



Image shown may not reflect actual package.

## STANDBY

**1280 ekW 1600 kVA**  
**50 Hz 1500 rpm 400 Volts**

Caterpillar is leading the power generation marketplace with Power Solutions engineered to deliver unmatched flexibility, expandability, reliability, and cost-effectiveness.

## FEATURES

### FUEL/EMISSIONS STRATEGY

- Low Fuel consumption

### DESIGN CRITERIA

- The generator set accepts 100% rated load in one step per NFPA 110 and meets ISO 8528-5 transient response.

### FULL RANGE OF ATTACHMENTS

- Wide range of bolt-on system expansion attachments, factory designed and tested
- Flexible packaging options for easy and cost effective installation

### SINGLE-SOURCE SUPPLIER

- Fully prototype tested with certified torsional vibration analysis available

### WORLDWIDE PRODUCT SUPPORT

- Cat dealers provide extensive post sale support including maintenance and repair agreements
- Cat dealers have over 1,800 dealer branch stores operating in 200 countries
- The Cat® S•O•S<sup>SM</sup> program cost effectively detects internal engine component condition, even the presence of unwanted fluids and combustion by-products

### CAT® 3512B TA DIESEL ENGINE

- Reliable, rugged, durable design
- Field-proven in thousands of applications worldwide
- Four-stroke-cycle diesel engine combines consistent performance and excellent fuel economy with minimum weight

### CAT SR5 GENERATOR

- Matched to the performance and output characteristics of Cat engines
- Industry leading mechanical and electrical design
- Industry leading motor starting capabilities
- High Efficiency

### CAT EMCP 4 CONTROL PANELS

- Simple user friendly interface and navigation
- Scalable system to meet a wide range of customer needs
- Integrated Control System and Communications Gateway

# STANDBY 1280 kW 1600 kVA

50 Hz 1500 rpm 400 Volts

## FACTORY INSTALLED STANDARD & OPTIONAL EQUIPMENT

System	Standard	Optional
Air Inlet	<ul style="list-style-type: none"><li>• Single element canister type air cleaner</li><li>• Service indicator</li></ul>	<ul style="list-style-type: none"><li><input type="checkbox"/> Dual element &amp; heavy duty air cleaners</li><li><input type="checkbox"/> Air inlet adapters &amp; shut-off</li></ul>
Cooling	<ul style="list-style-type: none"><li>• Radiator with guard</li><li>• Coolant drain line with valve</li><li>• Fan and belt guards</li><li>• Cat® Extended Life Coolant*</li></ul>	<ul style="list-style-type: none"><li><input type="checkbox"/> Radiator duct flange</li><li><input type="checkbox"/> Jacket water heater</li></ul>
Exhaust	<ul style="list-style-type: none"><li>• Dry exhaust manifold</li><li>• Flanged faced outlets</li></ul>	<ul style="list-style-type: none"><li><input type="checkbox"/> Mufflers and Silencers</li><li><input type="checkbox"/> Stainless steel exhaust flex fittings</li><li><input type="checkbox"/> Elbows, flanges, expanders &amp; Y adapters</li></ul>
Fuel	<ul style="list-style-type: none"><li>• Secondary fuel filters</li><li>• Fuel priming pump</li><li>• Flexible fuel lines</li><li>• Fuel cooler*</li></ul>	<ul style="list-style-type: none"><li><input type="checkbox"/> Water separator</li><li><input type="checkbox"/> Duplex fuel filter</li></ul>
Generator	<ul style="list-style-type: none"><li>• Class H insulation</li><li>• Cat digital voltage regulator (CDVR) with kVAR/PF control, 3-phase sensing</li><li>• Reactive droop</li></ul>	<ul style="list-style-type: none"><li><input type="checkbox"/> Oversize &amp; premium generators</li><li><input type="checkbox"/> Winding temperature detectors</li><li><input type="checkbox"/> Bearing temperature detectors</li><li><input type="checkbox"/> Anti-condensation heaters</li></ul>
Power Termination	<ul style="list-style-type: none"><li>• Bus bar (NEMA or IEC mechanical lug holes)</li><li>• Top cable entry</li></ul>	<ul style="list-style-type: none"><li><input type="checkbox"/> Circuit breakers, UL listed, 3 pole with shunt trip, 100% rated, manual or electrically operated</li><li><input type="checkbox"/> Circuit breakers, IEC compliant, 3 or 4 pole with shunt trip, manual or electrically operated</li><li><input type="checkbox"/> Bottom cable entry</li><li><input type="checkbox"/> Power terminations can be located on the right, left and/or rear as an option.</li></ul>
Governor	<ul style="list-style-type: none"><li>• ADEM™ 3</li></ul>	<ul style="list-style-type: none"><li><input type="checkbox"/> Load share module</li></ul>
Control Panels	<ul style="list-style-type: none"><li>• EMCP 4.2</li><li>• User Interface panel (UIP) - wall mounted</li><li>• AC &amp; DC customer wiring area (right side)</li><li>• Emergency stop pushbutton</li></ul>	<ul style="list-style-type: none"><li><input type="checkbox"/> Option for right or left mount UIP</li><li><input type="checkbox"/> Local &amp; remote annunciator modules</li><li><input type="checkbox"/> Digital I/O Module</li><li><input type="checkbox"/> Generator temperature monitoring &amp; protection</li><li><input type="checkbox"/> Remote monitoring software</li></ul>
Lube	<ul style="list-style-type: none"><li>• Lubricating oil and filter</li><li>• Oil drain line with valves</li><li>• Fumes disposal</li><li>• Gear type lube oil pump</li></ul>	<ul style="list-style-type: none"><li><input type="checkbox"/> Oil level regulator</li><li><input type="checkbox"/> Deep sump oil pan</li><li><input type="checkbox"/> Electric &amp; air prelube pumps</li><li><input type="checkbox"/> Manual prelube with sump pump</li><li><input type="checkbox"/> Duplex oil filter</li></ul>
Mounting	<ul style="list-style-type: none"><li>• Rails - Engine / generator / radiator mounting</li><li>• Rubber anti-vibration mounts (shipped loose)</li></ul>	<ul style="list-style-type: none"><li><input type="checkbox"/> Isolator removal</li><li><input type="checkbox"/> Spring-type vibration isolator (shipped loose)</li><li><input type="checkbox"/> IBC Isolators</li></ul>
Starting/Charging	<ul style="list-style-type: none"><li>• 24 volt starting motor(s)</li><li>• Batteries with rack and cables</li><li>• Battery disconnect switch</li></ul>	<ul style="list-style-type: none"><li><input type="checkbox"/> Battery chargers (5 or 10 amp)</li><li><input type="checkbox"/> 45 amp charging alternator</li><li><input type="checkbox"/> Oversize batteries</li><li><input type="checkbox"/> Ether starting aid</li><li><input type="checkbox"/> Heavy duty starting motors</li><li><input type="checkbox"/> Barring device (manual)</li></ul>

# STANDBY 1280 kW 1600 kVA

50 Hz 1500 rpm 400 Volts

## SPECIFICATIONS

### CAT GENERATOR

Cat Generator

Frame size..... 1468

Excitation..... Internal Excitation

Pitch..... 0.6667

Number of poles..... 4

Number of bearings..... Single bearing

Number of Leads..... 006

Insulation..... UL 1446 Recognized Class H with tropicalization and antiabrasion

Insulation..... Class F with tropicalization and antiabrasion

- Consult your Caterpillar dealer for available voltages

IP Rating..... IP23

Alignment..... Pilot Shaft

Overspeed capability..... 150

Wave form Deviation (Line to Line)..... 002.00

Voltage regulator..... 3 Phase sensing with selectable volts/Hz

Voltage regulation..... Less than +/- 1/2% (steady state)

Less than +/- 1% (no load to full load)

Telephone influence factor..... Less than 50

Harmonic Distortion..... Less than 5%

### CAT DIESEL ENGINE

3512B TA, V-12, 4-Stroke Water-cooled Diesel

Bore..... 170.00 mm (6.69 in)

Stroke..... 190.00 mm (7.48 in)

Displacement..... 51.80 L (3161.03 in<sup>3</sup>)

Compression Ratio..... 14.0:1

Aspiration..... TA

Fuel System..... Electronic unit injection

Governor Type..... ADEM3

### CAT EMCP 4 SERIES CONTROLS

EMCP 4 controls including:

- Run / Auto / Stop Control
- Speed and Voltage Adjust
- Engine Cycle Crank
- 24-volt DC operation
- Environmental sealed front face
- Text alarm/event descriptions

Digital indication for:

- RPM
- DC volts
- Operating hours
- Oil pressure (psi, kPa or bar)
- Coolant temperature
- Volts (L-L & L-N), frequency (Hz)
- Amps (per phase & average)
- kW, kVA, kVAR, kW-hr, %kW, PF

Warning/shutdown with common LED indication of:

- Low oil pressure
- High coolant temperature
- Overspeed
- Emergency stop
- Failure to start (overcrank)
- Low coolant temperature
- Low coolant level

Programmable protective relaying functions:

- Generator phase sequence
- Over/Under voltage (27/59)
- Over/Under Frequency (81 o/u)
- Reverse Power (kW) (32)
- Reverse reactive power (kVAr) (32RV)
- Overcurrent (50/51)

Communications:

- Six digital inputs (4.2 only)
- Four relay outputs (Form A)
- Two relay outputs (Form C)
- Two digital outputs
- Customer data link (Modbus RTU)
- Accessory module data link
- Serial annunciator module data link
- Emergency stop pushbutton

Compatible with the following:

- Digital I/O module
- Local Annunciator
- Remote CAN annunciator
- Remote serial annunciator

# STANDBY 1280 kW 1600 kVA

50 Hz 1500 rpm 400 Volts

## TECHNICAL DATA

Open Generator Set - - 1500 rpm/50 Hz/400 Volts	DM8045	
Low Fuel Consumption		
<b>Generator Set Package Performance</b> Genset Power rating @ 0.8 pf Genset Power rating with fan	1600 kVA 1280 kW	
<b>Coolant to aftercooler</b> Coolant to aftercooler temp max	30 ° C	86 ° F
<b>Fuel Consumption</b> 100% load with fan 75% load with fan 50% load with fan	323.3 L/hr 246.4 L/hr 170.7 L/hr	85.4 Gal/hr 65.1 Gal/hr 45.1 Gal/hr
<b>Cooling System<sup>1</sup></b> Air flow restriction (system) Engine Coolant capacity with radiator/exp. tank Engine coolant capacity Radiator coolant capacity	0.12 kPa 286.8 L 156.8 L 130.0 L	0.48 in. water 75.8 gal 41.4 gal 34.3 gal
<b>Inlet Air</b> Combustion air inlet flow rate	110.9 m <sup>3</sup> /min	3916.4 cfm
<b>Exhaust System</b> Exhaust stack gas temperature Exhaust gas flow rate Exhaust flange size (internal diameter) Exhaust system backpressure (maximum allowable)	393.7 ° C 260.0 m <sup>3</sup> /min 203.2 mm 6.7 kPa	740.7 ° F 9181.8 cfm 8.0 in 26.9 in. water
<b>Heat Rejection</b> Heat rejection to coolant (total) Heat rejection to exhaust (total) Heat rejection to aftercooler Heat rejection to atmosphere from engine Heat rejection to atmosphere from generator	502 kW 1092 kW 363 kW 114 kW 56.1 kW	28549 Btu/min 62102 Btu/min 20644 Btu/min 6483 Btu/min 3190.4 Btu/min
<b>Alternator<sup>2</sup></b> Motor starting capability @ 30% voltage dip Frame Temperature Rise	4282 skVA 1468 150 ° C	270 ° F
<b>Lube System</b> Sump refill with filter	310.4 L	82.0 gal
<b>Emissions (Nominal)<sup>3</sup></b> NOx mg/nm <sup>3</sup> CO mg/nm <sup>3</sup> HC mg/nm <sup>3</sup> PM mg/nm <sup>3</sup>	3223.1 mg/nm <sup>3</sup> 682.4 mg/nm <sup>3</sup> 68.0 mg/nm <sup>3</sup> 30.2 mg/nm <sup>3</sup>	

<sup>1</sup> For ambient and altitude capabilities consult your Cat dealer. Air flow restriction (system) is added to existing restriction from factory.

<sup>2</sup> UL 2200 Listed packages may have oversized generators with a different temperature rise and motor starting characteristics. Generator temperature rise is based on a 40 degree C ambient per NEMA MG1-32.

<sup>3</sup> Emissions data measurement procedures are consistent with those described in EPA CFR 40 Part 89, Subpart D & E and ISO8178-1 for measuring HC, CO, PM, NOx. Data shown is based on steady state operating conditions of 77°F, 28.42 in HG and number 2 diesel fuel with 35° API and LHV of 18,390 btu/lb. The nominal emissions data shown is subject to instrumentation, measurement, facility and engine to engine variations. Emissions data is based on 100% load and thus cannot be used to compare to EPA regulations which use values based on a weighted cycle.

# STANDBY 1280 ekW 1600 kVA

50 Hz 1500 rpm 400 Volts

## RATING DEFINITIONS AND CONDITIONS

---

**Meets or Exceeds International Specifications:** AS1359, CSA, IEC60034-1, ISO3046, ISO8528, NEMA MG 1-22, NEMA MG 1-33, UL508A, 72/23/EEC, 98/37/EC, 2004/108/EC

**Standby** - Output available with varying load for the duration of the interruption of the normal source power. Average power output is 70% of the standby power rating. Typical operation is 200 hours per year, with maximum expected usage of 500 hours per year. Standby power in accordance with ISO8528. Fuel stop power in accordance with ISO3046. Standby ambients shown indicate ambient temperature at 100% load which results in a coolant top tank temperature just below the shutdown temperature.

**Ratings** are based on SAE J1349 standard conditions. These ratings also apply at ISO3046 standard conditions. **Fuel rates** are based on fuel oil of 35° API [16° C (60° F)] gravity having an LHV of 42 780 kJ/kg (18,390 Btu/lb) when used at 29° C (85° F) and weighing 838.9 g/liter (7.001 lbs/U.S. gal.). Additional ratings may be available for specific customer requirements, contact your Cat representative for details. For information regarding Low Sulfur fuel and Biodiesel capability, please consult your Cat dealer.

# STANDBY 1280 ekW 1600 kVA

50 Hz 1500 rpm 400 Volts

## DIMENSIONS

---

Package Dimensions		
Length	5137.1 mm	202.25 in
Width	1974.9 mm	77.75 in
Height	2342.0 mm	92.2 in
Weight	12 896 kg	28,431 lb

NOTE: For reference only - do not use for installation design. Please contact your local dealer for exact weight and dimensions. (General Dimension Drawing #2882684).

Yellow Power Limited  
Haywood Mill  
Mill Lane  
Great Haywood  
Staffordshire, ST18 0RJ  
Tel: 01889 882255  
Web: [www.yellowpower.com](http://www.yellowpower.com)  
email: [sales@yellowpower.com](mailto:sales@yellowpower.com)