

---

## DIESEL GENERATOR SET



Image shown may not reflect actual package

## STANDBY 2480 kW 3100 kVA 50 Hz 1500 rpm 400 Volts

Caterpillar is leading the power generation Market place with Power Solutions engineered to deliver unmatched flexibility, expandability, reliability, and cost-effectiveness.

---

### FUEL/EMISSIONS STRATEGY

- Low BSFC

### DESIGN CRITERIA

- The generator set accepts 100% rated load in one step per NFPA 110 and meets ISO 8528-5 transient response.

### FULL RANGE OF ATTACHMENTS

- Wide range of bolt-on system expansion attachments, factory designed and tested
- Flexible packaging options for easy and cost effective installation

### SINGLE-SOURCE SUPPLIER

- Fully prototype tested with certified torsional vibration analysis available

### WORLDWIDE PRODUCT SUPPORT

- Cat<sup>®</sup> dealers provide extensive post sale support including maintenance and repair agreements
- Cat dealers have over 1,800 dealer branch stores operating in 200 countries.
- The Cat S•O•S<sup>SM</sup> program effectively detects internal engine component condition, even the presence of unwanted fluids and combustion by products.

### CAT<sup>®</sup> C175-16 DIESEL ENGINE

- Reliable, rugged, durable design
- Four-stroke diesel engine combines consistent performance and excellent fuel economy with minimum weight

### CAT SR5 GENERATOR

- Matched to the performance and output characteristics of Cat engines
- Single point access to accessory connections
- UL 1446 Recognized Class H insulation

### CAT EMCP 4 CONTROL PANELS

- Simple user friendly interface and navigation
- Scalable system to meet a wide range of customer needs
- Integrated Control System and Communications Gateway

**STANDBY 2480 ekW 3100 kVA**  
 50 Hz 1500 rpm 400 Volts

**FACTORY INSTALLED STANDARD & OPTIONAL EQUIPMENT**

System	Standard	Optional
Air Inlet	<ul style="list-style-type: none"> <li>• Air cleaner, 4 x single element canister with service indicator(s)</li> <li>• Plug group for air inlet shut-off</li> </ul>	<ul style="list-style-type: none"> <li><input type="checkbox"/> Air cleaner, 4 x dual element with service indicator(s)</li> <li><input type="checkbox"/> Air inlet adapters</li> </ul>
Cooling	<ul style="list-style-type: none"> <li>• SCAC cooling</li> <li>• Jacket water and AC inlet/outlet flanges</li> </ul>	<ul style="list-style-type: none"> <li><input type="checkbox"/> Remote horizontal SCAC radiator</li> <li><input type="checkbox"/> Remote fuel cooler</li> <li><input type="checkbox"/> Low coolant level sensor (for remote radiators)</li> </ul>
Exhaust	<ul style="list-style-type: none"> <li>• Dry exhaust manifold.</li> <li>• Bolted flange (ANSI 6" &amp; DIN 150) with bellow for each turbo (qty 4)</li> </ul>	<ul style="list-style-type: none"> <li><input type="checkbox"/> Engine Exhaust Temperature Module</li> <li><input type="checkbox"/> Mufflers (15 dBA, 25 dBA, or 40 dBA)</li> <li><input type="checkbox"/> Dual 16" or single 20" vertical exhaust collector</li> <li><input type="checkbox"/> Weld flange ANSI 20"</li> </ul>
Crankcase Systems	<ul style="list-style-type: none"> <li>• Open crankcase ventilation</li> </ul>	<ul style="list-style-type: none"> <li><input type="checkbox"/> Crankcase explosion relief valve</li> </ul>
Fuel	<ul style="list-style-type: none"> <li>• Primary fuel filter with water separator</li> <li>• Secondary fuel filters (engine mounted)</li> </ul>	
Generator SR5	<ul style="list-style-type: none"> <li>• 3 phase brushless, salient pole</li> <li>• IEC platinum stator RTD's</li> <li>• Cat digital voltage regulator (Cat DVR)</li> </ul>	<ul style="list-style-type: none"> <li><input type="checkbox"/> Space heater kit</li> <li><input type="checkbox"/> Oversize generators</li> <li><input type="checkbox"/> Power connection arrangement</li> </ul>
Governor	<ul style="list-style-type: none"> <li>• ADEM™ A4</li> </ul>	<ul style="list-style-type: none"> <li><input type="checkbox"/> Redundant shutdown</li> </ul>
Control Panels	<ul style="list-style-type: none"> <li>• EMCP 4.2</li> </ul>	<ul style="list-style-type: none"> <li><input type="checkbox"/> Local &amp; remote annunciator modules</li> <li><input type="checkbox"/> Discrete I/O module</li> <li><input type="checkbox"/> Generator temperature monitoring &amp; protection</li> <li><input type="checkbox"/> Remote monitoring</li> <li><input type="checkbox"/> Load share module</li> </ul>
Lube	<ul style="list-style-type: none"> <li>• Lubricating oil</li> <li>• Oil filter, filler and dipstick</li> <li>• Oil drain line with valves</li> <li>• Fumes disposal</li> <li>• Gear type lube oil pump</li> <li>• Integral lube oil cooler</li> </ul>	<ul style="list-style-type: none"> <li><input type="checkbox"/> Electric prelube pumps (standard for Prime and Continuous only)</li> </ul>
Mounting	<ul style="list-style-type: none"> <li>• Rails-engine / generator</li> <li>• Rubber anti-vibration mounts (shipped loose)</li> </ul>	<ul style="list-style-type: none"> <li><input type="checkbox"/> Spring type linear vibration isolators</li> <li><input type="checkbox"/> IBC vibration isolators</li> </ul>
Starting / Charging	<ul style="list-style-type: none"> <li>• Dual 24 volt electric starting motors</li> <li>• Batteries with rack and cables</li> <li>• Battery disconnect switch</li> </ul>	<ul style="list-style-type: none"> <li><input type="checkbox"/> Oversized battery set</li> <li><input type="checkbox"/> 75 amp charging alternator</li> <li><input type="checkbox"/> Battery chargers (20, 35 or 50 Amp)</li> <li><input type="checkbox"/> Jacket water heater</li> <li><input type="checkbox"/> Redundant Electric Starter</li> </ul>
Circuit Breakers		<ul style="list-style-type: none"> <li><input type="checkbox"/> Circuit breakers, UL 100% rated, 3 pole with shunt trip</li> <li><input type="checkbox"/> Circuit breakers, IEC rated, 3 or 4 pole with shunt</li> </ul>
General	<ul style="list-style-type: none"> <li>• RH service (Except LH Service Oil Filter)</li> <li>• Paint - Caterpillar Yellow with high gloss black rails</li> <li>• SAE standard rotation</li> <li>• Flywheel and flywheel housing - SAE No. 00</li> </ul>	<ul style="list-style-type: none"> <li><input type="checkbox"/> Barring group- manual or air powered</li> <li><input type="checkbox"/> Factory test reports</li> </ul>

**SPECIFICATIONS**

---

**CAT GENERATOR**

Frame ..... 1868  
Excitation .....PM  
Pitch.....0.6667  
Number of poles.....4  
Number of bearings .....2  
Number of Leads.....6  
Insulation .....Class H  
IP rating .....Drip proof IP22  
Over speed capability - % of rated.....125%  
Wave form deviation.....3 %  
Voltage regulator..... 3 phase sensing with load  
adjustable module

**CAT DIESEL ENGINE**

C175 SCAC, V-16, 4 stroke, water-cooled diesel

Bore .....175.00 mm (6.89 in)  
Stroke .....220.00 mm (8.66in)  
Displacement .....84.67 L (5166.88 in<sup>3</sup>)  
Compression ratio.....16.7:1  
Aspiration.....TA  
Fuel system.....Common Rail  
Governor Type.....ADEM™ A4

**CAT EMCP 4 SERIES CONTROLS**

EMCP 4 controls including:

- Run / Auto / Stop Control
- Speed and Voltage Adjust
- Engine Cycle Crank
- 24-volt DC operation
- Environmental sealed front face
- Text alarm/event descriptions

Digital indication for:

- RPM
- DC volts
- Operating hours
- Oil pressure (psi, kPa or bar)
- Coolant temperature
- Volts (L-L & L-N), frequency (Hz)
- Amps (per phase & average)
- ekW, kVA, kVAR, kW-hr, %kW, PF

Warning/shutdown with common LED indication of:

- Low oil pressure
- High coolant temperature
- Overspeed
- Emergency stop
- Failure to start (overcrank)
- Low coolant temperature
- Low coolant level

Programmable protective relaying functions:

- Generator phase sequence
- Over/Under voltage (27/59)
- Over/Under Frequency (81 o/u)
- Reverse Power (kW) (32)
- Reverse reactive power (kVAr) (32RV)
- Overcurrent (50/51)

Communications:

- Six digital inputs (4.2 only)
- Four relay outputs (Form A)
- Two relay outputs (Form C)
- Two digital outputs
- Customer data link (Modbus RTU)
- Accessory module data link
- Serial annunciator module data link
- Emergency stop pushbutton

Compatible with the following:

- Digital I/O module
- Local Annunciator
- Remote CAN annunciator
- Remote serial annunciator

**TECHNICAL DATA**

Open Generator Set - 1500 rpm/50 Hz/400 Volts	STANDBY DM8725	
<b>Package Performance</b> Power rating Power rating @ 0.8 pf	2480 ekW 3100 kVA	
<b>Fuel Consumption</b> 100% load with fan 75% load with fan 50% load with fan	609.5 L/hr 457.3 L/hr 317.2 L/hr	160.9 Gal/hr 120.7 Gal/hr 83.8 Gal/hr
<b>Cooling System*</b> Coolant to aftercooler temp max	48° C at 30° C ambient 118° C at 86° F ambient	
<b>Inlet Air</b> Combustion air inlet flow rate	187.0 m <sup>3</sup> /min	6607.4 cfm
<b>Exhaust System</b> Exhaust stack gas temperature Exhaust gas flow rate Exhaust flange size (internal diameter) Exhaust system backpressure (maximum allowable)	484.9 °C 492.7 m <sup>3</sup> /min 150 mm 6.7 kPa	904.8 °F 17405.5 cfm 6 in 26.9 in. water
<b>Heat Rejection</b> Heat rejection to coolant (total) Heat rejection to exhaust (total) Heat rejection to aftercooler Heat rejection to atmosphere from engine Heat rejection to atmosphere from generator	1146.7 kW 2230.1 kW 217.1 kW 262.4 kW 103.3 kW	65227 Btu/min 126895 Btu/min 12350 Btu/min 14924 Btu/min 5875 Btu/min
<b>Alternator**</b> Motor starting capability @ 30% voltage dip Frame Temperature Rise	7645 SKVA 1868 150°C	270 °F
<b>Lube System</b> Lube oil refill volume with filter change for standard sump	540 L	142.6 US Gal
<b>Emissions (Nominal)***</b> NO <sub>x</sub> CO HC PM	7.79 g/hp-hr 0.32 g/hp-hr 0.13 g/hp-hr 0.03 g/hp-hr	4136.4 mg/nm <sup>3</sup> 152.4 mg/nm <sup>3</sup> 54.3 mg/nm <sup>3</sup> 11.2 mg/nm <sup>3</sup>

Note: This generator set package is not offered with an engine driven radiator.  
The addition of an engine driven fan will reduce the output below the nameplate rating.

\* For ambient and altitude capabilities consult your Cat dealer. Air flow restriction (system) is added to existing restriction from factory.

\*\* UL 2200 Listed packages may have oversized generators with a different temperature rise and motor starting characteristics. Generator temperature rise is based on a 40 degree C ambient per NEMA MG1-32.

\*\*\* Emissions data measurement procedures are consistent with those described in EPA CFR 40 Part 89, Subpart D & E and ISO8178-1 for measuring HC, CO, PM, NO<sub>x</sub>. Data shown is based on steady state operating conditions of 77°F, 28.42 in HG and number 2 diesel fuel with 35° API and LHV of 18,390 btu/lb. The nominal emissions data shown is subject to instrumentation, measurement, facility and engine to engine variations. Emissions data is based on 100% load and thus cannot be used to compare to EPA regulations which use values based on a weighted cycle.

## **RATING DEFINITIONS AND CONDITIONS**

---

**Meets or Exceeds International Specifications:**  
AS1359, CSA, IEC60034-1, ISO3046, ISO8528, NEMA  
MG 1-22, NEMA MG 1-33, UL508A, 72/23/EEC,  
98/37/EC, 2004/108/EC

**Standby** - Output available with varying load for the duration of the interruption of the normal source power. Average power output is 70% of the standby power rating. Typical operation is 200 hours per year, with maximum expected usage of 500 hours per year. Standby power in accordance with ISO8528. Fuel stop power in accordance with ISO3046. Standby ambients shown indicate ambient temperature at 100% load which results in a coolant top tank temperature just below the shutdown temperature.

**Prime** - Output available with varying load for an unlimited time. Average power output is 70% of the prime power rating. Typical peak demand is 100% of prime rated ekW with 10% overload capability for emergency use for a maximum of 1 hour in 12. Overload operation cannot exceed 25 hours per year. Prime power in accordance with ISO3046. Prime ambients shown indicate ambient temperature at 100% load which results in a coolant top tank temperature just below the alarm temperature.

**Continuous** – Output available with non-varying load for an unlimited time. Average power output is 70-100% of the continuous power rating. Typical peak demand is 100% of continuous rated ekW for 100% of operating hours. Continuous power in accordance with ISO3046. Continuous ambients shown indicate ambient temperature at 100% load which results in a coolant top tank temperature below the alarm temperature.

**Ratings** are based on SAE J1349 standard conditions. These ratings also apply at ISO3046 standard conditions

**Fuel Rates** are based on fuel oil of 35° API [16° C (60° F)] gravity having an LHV of 42 780 kJ/kg (18,390 Btu/lb) when used at 29° C (85° F) and weighing 838.9 g/liter (7.001 lbs/U.S. gal.). Additional ratings may be available for specific customer requirements, contact your Caterpillar representative for details. For information regarding Low Sulfur fuel and Biodiesel capability, please consult your Cat dealer.

# STANDBY 2480 ekW 3100 kVA

50 Hz 1500 rpm 400 Volts



## DIMENSIONS

---

Package Dimensions		
Length	6631.6 mm	261.1 in
Width	2089.4 mm	82.3 in
Height	2207.9 mm	86.9 in

NOTE: For reference only - do not use for installation design. Please contact your local dealer for exact weight and dimensions.